



- All-round Full HD zoom camera with 3x zoom
- PoE+, 24 VDC or 24 VAC
- Including wall / ceiling mount bracket
- Zones 1, 2, 21, 22
- Day / night, WDR, ONVIF S and Q
- Available without cable or with a 4 m or 10 m long armoured multi-cable

A9

WebCode **EC910AFZA**



The EC-910-AFZ PoE+ camera combines state-of-the-art camera technology with Full HD resolution, WDR and zoom function for hazardous areas. The light-sensitive 3x zoom version features an extreme viewing angle of up to 90° (horizontal), making it ideal for monitoring rooms or inspection windows. To ensure guaranteed resistance to adverse weather, the EC-910-AFZ with 3x zoom has been tested and certified by Lloyd's Register for marine application. Lloyd's attests the camera's reliability with regard to temperature, corrosion and vibration resistance as well as EMC. Their design makes the cameras universally applicable in the oil and gas industries and in the chemical, pharmaceutical and related industries. The camera is certified acc. to ATEX, IECEx for Zone 1, 2, 21, 22. Additional certificates available are NEC C1 D2, CEC C1 Z1, EAC. The stainless-steel sun-protection and the wall / ceiling mount bracket are part of the standard delivery.




	IECEx / ATEX					
Zone	0	1	2	20	21	22
Installation in		•	•		•	•

	NEC 500 CEC Appendix J					
	Class I		Class II		Class III	
Division	1	2	1	2	1	2
Installation in		•		•		

	CEC Section 18					
	NEC® 505			NEC® 506		
	Class I					
Zone	0	1	2	20	21	22
Installation in		•	•		•	•

Selection Table						
Focus	Automatic focus					
Zoom	3x optical					
Resolution	Full HD to 320x180p					
Viewing angle	90° (wide), 32° (tele.)					
Network protocol	ONVIF profile S and Q					
Product Type	Connection cable	Cable length	Certifications	Art. No.	Weight	kg
EC-910-AFZ-I03-P00	without cable	0 m	ATEX, IECEx, EAC, NEC, CEC	264963	6.500	
EC-910-AFZ-I03-P04	with cable	4 m	ATEX, IECEx, EAC	265897	8.500	
EC-910-AFZ-I03-P10	with cable	10 m	ATEX, IECEx, EAC	265898	11.500	

Accessories				
Figure	Description	Art. No.	Weight	kg
Pole and Corner module EC-910				
	Pole and Corner module EC-910-AFZ Stainless steel 316L, electropolished Payload: 30 kg Pole diameter: 60 mm ... 200 mm Dimension: 120 x 86 mm	264965	1.000	

Accessories			
Figure	Description	Art. No.	Weight kg
Ex e Terminal box			
	JCT-8146-Ethernet+Analog 5xcable glands Terminal box, polyester resin Version for ethernet or analog cameras 5 x cable glands: 2 x CMP-25SC2KVAR KLE MsNi M25x1.5 1 x 8161/7-M25-1707 with red stopping plug 2 x 8161/7-M20-1304 with red stopping plug usable for: EC-750, EC-910-AFZ, EC-940S-AFZ (ATEX, IECEx) EC-840S-TIC (ATEX, IECEx), EC-940-PTZ, Water tank	265668	0.800
Camera multi-cable armoured			
	VB-CAM-MULTI-Ethernet-ARM 1 x Ethernet cable 3 x power supplies 2.5 mm ² 7 x data cable 0.34 mm ² -60 °C ... +80 °C 19.2 ±0.5 mm outer diameter IEC 60332-1 flame-resistant IEC 60754-2 halogen-free DIN 60811-404 oil-resistant NEK 606 mud-resistant Price per metre	252571 ▲	0.472
Cable glands			
	CMP-20PX2K-REX-MsNi-NPT 1/2" OR-SET Cable gland with RapidEx compound explosion-protected Clamping-range: 12.5 ... 20.9 mm for EC-910	275571	0.425
	CMP-20sPX2K-REX KLE MsNi NPT 1/2" OR-SET Cable gland with RapidEx compound explosion-protected Clamping-range: 12.5 ... 20.9 mm for EC-910	278866	0.425
	CMP-20sPXSS2K-REX KLE MsNi NPT 1/2" SET Cable gland with RapidEx compound explosion-protected Clamping-range: 6.1 mm ... 11.7 mm for EC-910 and water tank	279480	0.375

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations

A9

