

717e Ex

717e NYLON UNIVERSAL STOPPER PLUG, EXPLOSIVE ATMOSPHERE Ex e CONDUIT ACCESSORY

- Provides means of blanking unused cable entries
- Cost effective moulded design
- Universal tightening design (hex head, allen key and slotted/flat screw head)
- Temporary or permanent
- Available in blue for intrinsically safe circuits
- Approved entry thread sealing washer available
- -60 to +95°C



Ex eb Ex ta

COLOUR	SUFFIX	METRIC ORDERING EXAMPLE	NPT ORDERING EXAMPLE
BLACK - RAL9011	-	717EM2	717ET1
BLUE - RAL5015	4	717EM24	717ET14

TECHNICAL CLASSIFICATION		
INGRESS PROTECTION RATING		*MINIMUM IP68 DEPTH AND DURATION
WITHOUT ENTRY THREAD SEAL FITTED	IP66,IP67,IP68**,IP69,IP69K	1.1 metres for 16 hours**
WITH ENTRY THREAD SEAL FITTED	IP66,IP67,IP68**,IP69,IP69K	30 metres for 16 hours**
AVAILABLE MATERIALS	Halogen-free Polyamide	
CONTINUOUS OPERATING TEMPERATURE	-60°C to +95°C	

**Alternative depths / durations can be provided upon request.

GLOBAL PRODUCT CERTIFICATION			
ATEX CERTIFICATE	CML20ATEX3054X	IECEX CERTIFICATE	IECEX CML20.0038X
UKEX CERTIFICATE	CML21UKEX3237X		
CODE OF PROTECTION	Ⓔ II 2G ID Ex eb IIC Gb, Ex ta IIIC Da	CODE OF PROTECTION	Ex eb IIC Gb, Ex ta IIIC Da
COMPLIANCE STANDARDS	EN 60079-0, 7, 31	COMPLIANCE STANDARDS	IEC 60079-0, 7, 31
EAC CERTIFICATE	RU C-GB.A, I 07.B.02495/20	CCC CERTIFICATE	2020522513001727

DESCRIPTION	ALLEN KEY RECESS	METALLIC			NON-METALLIC	
		Ex 'd'	Ex 'e'	INDUSTRIAL	Ex 'e'	INDUSTRIAL
747 RECESSED NON-TAMPER PROOF TYPE 'A'	✓	✓	✓	✓	✓	✓
747 RECESSED TAMPER-PROOF TYPE 'B'	✓	✓	✓	✓	✓	✓
757 HEXAGON HEAD	x	✓	✓	✓	✓	✓
757 HEXAGON HEAD C/W O-RING SEAL	x	✓	✓	✓	✓	✓
767 DOME HEAD	✓	✓	✓	✓	✓	✓
767 DOME HEAD C/W O-RING SEAL	✓	✓	✓	✓	✓	✓
717 UNIVERSAL	✓	x	x	x	✓	✓

PRODUCT SELECTION TABLE - METRIC						
ORDERING REFERENCE	THREAD SIZE	MINIMUM THREAD LENGTH	ACROSS FLATS	ACROSS CORNERS DIAMETER	PROTRUSION LENGTH	ALLEN KEY SIZE
717EM2	M20	10.0	24.0	26.3	7.0	8
717EM3	M25	10.0	28.0	30.7	7.0	10
717EM4	M32	10.0	38.0	41.7	8.0	10

All dimensions shown are in millimetres unless otherwise stated

Ordering reference shown for black metric product

PRODUCT SELECTION TABLE - NPT						
ORDERING REFERENCE	THREAD SIZE	MINIMUM THREAD LENGTH	ACROSS FLATS	ACROSS CORNERS DIAMETER	PROTRUSION LENGTH	ALLEN KEY SIZE
717ET1	1/2"	14.0	24.0	26.3	7.0	8
717ET2	3/4"	14.0	28.0	30.7	7.0	10
717ET3	1"	14.0	38.0	41.7	8.0	10

All dimensions shown are in millimetres unless otherwise stated

Ordering reference shown for black NPT product
For additional sizes please refer to stopper plug range at www.cmp-products.com